


GNR-3000

64-Channel Desktop Standalone NVR




- 5-bay Desktop with software RAID (0,1)
- Manage up to 64 cameras or video encoders
- Recording up to 64 Channels
- Live view local up to 16 Channels, remote up to 64 Channels
- Synchronized playback local up to 9 Channels, remote up to 64 Channels
- Export video with RAW and AVI formats
- Event trigger, response and notification
- Mobile Client, Web Client, Workstation
- Location-based management with eMap
- 32-channel free license included
- Non-ACTi camera support via licensed Camera Device Pack

PHOTO INDICATION




DIMENSION DIAGRAM



Unit: mm [inch]

SOLUTION ARCHITECTURE

Standalone NVR



PRODUCT SPECIFICATION**GNR-3000****• General**

Full Name	ACTi Standalone Network Video Recorder GNR-3000
Maximum Number of Clients	4* (without local client)
Maximum Number of Cameras	64
Free License	32 Channels
Compression	H.264, MPEG-4, MJPEG
Maximum local display resolution	1920x1200

• Live View

Display Layout Mode	4:3 monitor: 1, 4, 5, 6, 8, 9, 10, 16, 25, 36, 49, 64 16:9 wide screen monitor: 1, 4, 6, 9, 12, 18, 24, 35, 48, 64
View Manager	An interface to define display layouts and the pre-set cameras within layout in the public or private view
View Patrol	Automatic switch between different views or devices
View Panel	Contains the list of pre-defined views for quick launch
Digital Zoom	Zoom in/out digitally by PiP (Picture-in-Picture)
Camera Tree	Drag and drop video source from camera tree into display layout; display camera status on the tree
Manual Recording / Snapshot	Instant recording upon mouse click / Instant snapshot upon mouse click or hot key
Event Panel	Display event status upon alarm or upon connection loss or recovery
Two-way Audio	Audio sound from and to all the audio supported devices; audio broadcast to multiple devices at the same time
Dual Stream Management	Live view of stream 1 or stream 2 of dual stream devices
Instant Playback	Instant playback in live view window

• e-Map

Layout	Area maps with camera icons, small live view windows; hyperlinked
Map Switch and Tour	Manual switch and auto tour modes selectable
Setup	e-Map image upload; camera positioning; map linking
PTZ Mode	Mouse PTZ mode to control e-Map video streams

• PTZ

Control	Pan, tilt and zoom controls; speed control; both buttons and mouse controls
Preset Points and Tours	Create preset points; create auto tours between preset points
Number of Preset Points	32
Joystick	USB based joystick supported
Default Protocol	Auto-detect camera's PTZ protocol. Available protocols: ACTi, Pelco-P, Pelco-D, Dynacolor, Visca

• Recording

Scheduled Recording	Record video with user defined schedule
Event Recording	Record video when the alarm event is triggered, including the pre-event buffered video clip
Speed Up	Different recording frame rate settings for non-event and triggered event
Manual Recording	Instant recording upon mouse click
Dual Stream Management	Recording of stream 1 or stream 2 of dual stream devices
Recording Frame Rate	Max 1920 fps total; Max 30 fps per camera
Maximum Recording Throughput	300 Mbps

• Storage

Interface	Serial ATA
HDD Bay	Maximum 5 disks (1 system disk included)
RAID Level	Software RAID 0, 1
External Storage Support	eSATA, iSCSI, USB mass storage

• Search & Playback

Time Based Video Search	Search video recordings by time or channel
Event Based Video Search	Search alarm triggered video recordings
Playback Control	Continuous forward and backward playback with speeds 1x/2x/4x/8x or frame-by-frame; pause; stop
Synchronized Playback	Up to 9 channels for local display; up to 64 channels for remote client
Manual Snapshot	Instant snapshot from playback upon mouse click
Digital Zoom	Zoom in/out digitally by PiP (Picture-in-Picture)
Video Cropping	Crop a short video clip from long recording file and save it as an independent file
Video Export	Export video clips in AVI or RAW format; text overlay supported

• Event Management

Event Trigger	Video motion detection; Passive IR sensor; External device through digital input; Network loss and recovery; Server loss and recovery; Disk full; Disk not found
Event Response	Record video; Pop-up window with live video; Switch to hotspot window; Play beep sound; Activate external device through digital output; Upload snapshot to FTP server; Execute system command to activate other programs; E-mail notification with snapshots; Command a PTZ device to go to a preset point
Manual Event	Manually activate external devices through digital output via live view monitor
Scheduler	Define the schedule of event manager

• System

Permission Control	Multi-group/users, liveview/playback/setup/remote level permission
Operating System	Win 7 Std. Embedded
Language	Multi-language support

GNR-3000

Standalone NVR

• Remote Access

PC Client Program	User interface program (Workstation) with live view, PTZ, playback, e-Map, event management, setup
PC Web Browser	Microsoft Internet Explorer 8.0 or 9.0 with live view, PTZ, playback, event management, setup
Mobile Client Program	Mobile device application (MobileGo) supports live view, PTZ control, event or time based search and playbackSupported devices: iPhone, iPad, iPod Touch
Remote Client PC	1-16 channels: Intel Core 2 Quad 2.4GHz, 4GB RAM 17-64 channels: Intel Core i7-920 2.67 GHz, 4GB RAM

• Hardware

Dimensions (W x H x D)	200 mm x 215 mm x 313.5 mm (7.9" x 8" x 12")
Weight	3.88 kg (8.55 lb) without HDD
Operating Temperature	0°C~ 40°C(32°F ~ 104°F)
Operating Humidity	10% ~ 85% RH
Power Source / Consumption	110V~220V AC 50/60Hz /200W
Approvals	CE (EN 55022 Class B, EN 55024), FCC (Part15 Subpart B Class B)
USB	USB 2.0, 4 ports
Ethernet Port	2, Ethernet (1000 Base-T), RJ-45 connector
Display port	VGA

• Integration

Unified Solution	Fully compatible with ACTi cameras, encoders and CMS2.0
Open Platform Solution	Support ONVIF compliant devices