

KT-KD31 live video switcher

8 channels, SDI/HDMI/IP, RTMP live streaming

Features

*Multi-channel input, up to 4 channels of 3G-SDI+2 channels of HDMI+2 channels of IP, a total of 8 channels of video input, which can be adapted to a variety of live broadcast environments

*Volume control, body integrated volume control fader, support for output volume control

*High-definition display, the body integrates an 11.6-inch high-definition display, no need to connect an external preview large screen, simplifying the process of setting up a live broadcast environment

- * Various transition effects
- * Subtitle overlay
- * Logo overlay
- *Picture in Picture



Parameter	
Video standard	FHD
Video processing capabilities	Input: Max 1920x1080p60 Output: Max 1920x1080p60
Video input	4 channels 3G-SDI+2 channels HDMI+2 channel IP video streaming
Video output	2 channels 3G-SDI+1channelsHDMI+2channels IP video streaming
Live video encoding format	H.264、H.265
Live video bitrate	500~10240Kbps
Live video bitrate mode	CBR
Network input protocol	RTSP、RTMP
Network output protocol	RTSP、RTMP
Audio input	RCA head*1

	TRS3.5mm*1 Video embedded
Audio output	RCA *1 TRS 3.5mm*1 Video embedded
Transition control	T-Bar、button
Subtitle overlay	support
Logo overlay	support
USB port	USB3.0*2+USB2.0*2
Power supply	
Input voltage	DC 12V
Input Current	3A
Rated power	36W
Others	
Use environment	Indoor
Operating temperature	0°C~40°C
Storage temperature	-10°C~50°C
Dimensions	420*257.52*121.2mm