

# KT-UH62RKS

4K Ultra HD camera

TALLY

EXT SYNC

FULL NDI

6G-SDI



## Features

### ■ 4K Ultra HD Resolution:

Apply SONY 1/2.8" Progressive CMOS sensor, 8.50 Megapixels, can reach 4K (3840x2160) high resolution with frame rate up to 4K 30fps.

### ■ Abundant Outputs:

Support HDMI, USB3.0, 6G-SDI, LAN output in sync.

Support SYNC signal input.

### ■ Ultra High Frame Rate:

Support HDMI, 6G-SDI, LAN, USB3.0 video output frame rate can reach 4K 30fps.

### ■ 72.5° Wide Angle+16x digital zoom:

Apply high quality 8.50 megapixels 4K ultra wide-angle lens, 12x optical zoom, support 16x digital zoom.

### ■ Low Light:

Brand new CMOS image sensor with ultra high S/N Ratio can effectively reduce image noise in low light conditions. Applying 2D&3D Digital noise reduction at the same time, it reduces image noise greatly, even in ultra low light conditions, it could still remain the frame clean and clear, S/N Ratio of the image is higher than 55dB.

### ■ Signal transparent transmission function of infrared remote controller:

Apart from receiving its own infrared remote controller's signals, it can also receive signals of the consumer's infrared remote controller and send to video conference terminal via VISCA IN port.

### ■ Multi-installation Methods:

Wall mounting, desktop or ceiling mounting.

## Specifications

Camera	
Resolution	2160p/30/25, 1080p60/50, 1080p30/25, 1080i60/50, 720p60/50
Image Sensor	SONY 1/2.8" Progressive CMOS
Scan Mode	Line by line
Lens	12X optical zoom, f=3.9mm(w)~46.8mm(f)
Focus System	Auto/Manual
Minimum Illumination	0.5 Lux @ (F1.8, AGC ON)
Shutter Speed	1/25s~1/10000s
White Balance	Auto/Manual/One-click/Indoor/Outdoor
Backlight Compensation	Support
Digital Noise Reduction	2D&3D Digital noise reduction
S/N Ratio	≥55dB
Horizontal View Angle	72.5°(W)~6.5°(T)
Vertical View Angle	40.8°~3.7°
Horizontal Rotation Range	355°
Vertical Rotation Range	-30°~+90°
Horizontal Rotation Speed Range	1°~60°/s
Vertical Rotation Speed Range	1°~60°/s
Electronic Flip	Support
Image Freeze	Support
POE Power Supply	802.3af(optional)
Preset Position	9 preset positions by IR remote controller, 200 preset positions by joystick controller or PC
Accuracy of Preset Position	0.1°±10%
Network Characteristics	
Code Stream	Main code stream*1, Auxiliary code stream*1
Coding Format	H.264, H.265, MJPEG
Streaming Media Protocol	RTMP, RTSP, RTMPS, ONVIF, FULL NDI, SRT
Main Code Stream Resolution	576P30, 720P25, 720P30, 1080P25, 1080P30, 2160P25, 2160P30
Auxiliary Code Stream Resolution	576P30, 720P25, 720P30

Interface	
Video Output HD	1 Line, HDMI: Version1.4
	1 Line, 6G-SDI: SMPTE-2081, SMPTE-274M(Level A), SMPTE-296M
Synchronous Input	EXT/INT, BNC, 75Ω
Network Interface	1 Line, RJ45: 10M/100M/1000M Ethernet port
Control Mode	1 Line, RS232 IN: 8 Pin Mini Din, up to 30 meters, VISCA/Pelco-D/Pelco-P Protocol
	1 Line, RS232 OUT: 8 Pin Mini Din, up to 30 meters, VISCA/Pelco-D/Pelco-P Protocol
	1 Line, RS422/485 IN/OUT: Nine-core Phoenix Interface, up to 1200 meters, VISCA/Pelco-D/Pelco-P Protocol
Power Interface	DC 12V IEC60130-10(JEITA Standard RC-5320A) TYPE4
General Specifications	
Input Voltage	DC 12V
Input Current	Max.1.5A
Power Consumption	Max.18W
Operating Temperature	0~40℃
Storage Temperature	-10-60℃
Camera Dimensions	(L)170×(W)151×(H)190mm
Color	Black
Weight	1500g
Accessories	DC 12V power adapter, IR Remote, Operation manual, RS-232C Cable, 4K HDMI Cable, Ceiling bracket (Wall bracket optional)