

# Z415

## 2MP Zoom Bullet with D/N, Adaptive IR, Extreme WDR, SLLS, 10x Zoom Lens



- 2 Megapixel
- Day & Night with Superior Low Light Sensitivity and Adaptive IR LED
- Extreme WDR (145dB)

### ► Specifications

#### Device

Product Type	Zoom Bullet
Maximum Resolution	2MP
Application Environment	Outdoor
Image Sensor	Progressive Scan CMOS
Sensor Size	1/2.8 "
Day / Night	Yes
Low Light Sensitivity	Superior
Minimum Illumination	Color: 0.002 lux at F1.6 (AGC on); B/W: 0 lux (IR LED on)
Mechanical IR Cut Filter	Yes
IR LED	Adaptive IR LED (850 nm)
IR Working Distance	100m
Electronic Shutter	1-1/100000 second (manual mode); 1-1/100000 second (auto mode)
S/N Ratio	75 dB

#### Lens

Focal Length	Zoom, f5.0-50mm
--------------	-----------------

Aperture	F1.6
Zoom Ratio	10x optical zoom, 10x digital zoom
Iris	DC iris
Horizontal Viewing Angle	55.87° - 4.71°
Vertical Viewing Angle	68.72° - 5.56°
Viewing Angle Adjustment	Pan: 0°-360°, Tilt: 0°-90°, Rotation: 0°-360°

## Video

Compression	H.265 Adaptive Stream (equivalent to Zip or Smart Stream or H.265+), H.264 (Baseline/ Main/ High profile), MJPEG
Maximum Frame Rate vs. Resolution	60 fps at 1920 x 1080 60 fps at 720 x 576
Multi-Streaming	Simultaneous triple streams
Bit Rate	128Kbps - 16Mbps (per stream)
Bit Rate Mode	Constant, Variable
Wide Dynamic Range	Extreme WDR (145 dB)
Image Enhancement	White Balance, Backlight compensation (BLC), Highlight compensation (HLC)
Digital Noise Reduction	2D + 3D DNR
Privacy Mask	4 configurable regions
Text Overlay	Yes
Built-in Analytics	Face Detection, Age Detection, Gender Detection, Face Mask Detection, People Counting, Crowd Detection, Object Line Crossing Detection, Object Enter Area Detection, Object Exit Area Detection, Intrusion Detection (Forbidden Area Detection), Missing Object Detection, Unattended Object Detection, Tampering Detection
Image Orientation	Flip, Mirror, Rotation (Corridor mode)(±90°, 180°)

## Audio

Audio Type	2-way, Line-in, Line-out
Audio Compression	G.711

## Network

Network Protocol & Service	IPv4/v6, TCP, UDP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, NTP, RTP, RTSP, RTCP, RTMP, SMTP, IGMP, ICMP, ARP, UPnP, SNMP, QoS, SSL/TLS, IEEE 802.1X
Ethernet Port	1 x Ethernet (10/100 Base-T), RJ-45 connector
Maximum User Connections	32
Security	IP address filtering, HTTPS encryption, Password protected user level

## Event

Event Trigger	Video motion detection, Sound detection, Tampering detection, External device through digital input,
---------------	--

## Integration

ONVIF Compliant	Yes, Profile S, Profile G, Profile T
Web Browser	IE 11, Microsoft Edge, Google Chrome, Firefox


**Interface**

Serial Port	1 x RS-485
Analog Video Output	1 x BNC connector
Digital Input/Output	2/1
Operating Button	Reset Button

**General**




Power Source	DC 12V, High PoE (IEEE802.3at)
Power Consumption	13 W (PoE)
Weight	1930g (4.25lb)
Dimensions	(L x W x H): 354mm x 105mm x 98mm (13.9" x 4.1" x 3.9")
Environmental Casing	Weatherproof (IP67), Vandal proof metal casing (IK10)
Corrosion Protection	Ordering Number will be created upon orders.. Chassis corrosion resistance at the seashore approximately 2-3 years.
Bundled Accessories	Junction Box
Heater	Yes
Operating Temperature	-40°C ~ 60°C (-40°F ~ 140°F)
Surge Protection	6KV
Approvals	CE, FCC, IP67, IK10 (metal casing)

**► Related Products****Mounting Accessories - Camera Mount**


PMAX-0527	 Pole Mount (for Z4x, Z710, Z8x, Z9x, A7x), supports 2.64" to 5" Poles
-----------	---

**Note:** Some mounting accessories may need additional accessories for installation. Please check [www.acti.com/mountingselector](http://www.acti.com/mountingselector) for more information.

**Power Supply Accessories - Power Adapter**

PPBX-0013	 Power Adapter AC 100~240V (EU), for A3x, A4x, A88, A9x, Z31, Z8x, Z9x
PPBX-0014	 Power Adapter AC 100~240V (UK), for A3x, A4x, A88, A9x, Z31, Z8x, Z9x
PPBX-0023	 Power Adapter 12V /2A(US) with DC PLUG for A416, A418

**Power Supply Accessories - PoE Injector**

PPOE-0107	 High PoE Injector IEEE 802.3at compliant, AC 100~240V, with universal connectors (for A416, A418, B913, B923, B934, Q450, Q75, VMGB-60X, Z37, Z71, Z952)
-----------	--

Illuminators - IR LED Illuminator

PLED-0210

