

# Z721

## 4MP LightGuard 2.8mm Outdoor Mini Dome with D/N, Adaptive IR, Extreme WDR, SLLS, M12,



- 4 Megapixel
- LightGuard
- Day & Night with Superior Low Light Sensitivity and Adaptive IR LED
- Fixed Lens, f2.8mm/F1.6
- Extreme WDR (135dB)
- Super wide angle
- Weatherproof (IP67), Vandal proof (IK10), Vibration proof (EN50155)
- Event trigger, response and notification

### ► Specifications

#### Device

|                          |  |
|--------------------------|--|
| Product Type             | Mini Dome  |
| Maximum Resolution       | 4MP  |
| Application Environment  | Outdoor  |
| Image Sensor             | Progressive Scan CMOS  |
| Sensor Size              | 1/3 "  |
| Day / Night              | Yes  |
| Low Light Sensitivity    | Superior   |
| Minimum Illumination     | Color: 0.002 lux at F1.6 (AGC on); B/W: 0 lux (IR LED on)      |
| LightGuard               | Yes  |
| Mechanical IR Cut Filter | Yes  |
| IR LED                   | Adaptive IR LED (850 nm)                                       |
| IR Working Distance      | 30m  |
| Electronic Shutter       | 1-1/100000 second (manual mode); 1-1/100000 second (auto mode) |
| S/N Ratio                | 75 dB  |

## Lens

|                          |  |
|--------------------------|--|
| Focal Length             | Fixed focal, f2.8mm                          |
| Aperture                 | F1.6   |
| Horizontal Viewing Angle | 101.1°                                       |
| Vertical Viewing Angle   | 55.3°  |
| Viewing Angle Adjustment | Pan: 0°-90°, Tilt: 0°-68°, Rotation: 0°-360° |

## Video

|                                   |   |
|-----------------------------------|---|
| Compression                       | H.265 Adaptive Stream (equivalent to Zip or Smart Stream or H.265+), H.264 Adaptive Stream (equivalent to Zip or Smart Stream or H.264+), MJPEG   |
| Maximum Frame Rate vs. Resolution | 30 fps at 2688 x 1520 30 fps at 2560 x 1440 30 fps at 2304 x 1296 30 fps at 1920 x 1080 30 fps at 1280 x 720 30 fps at 720 x 576 30 fps at 640 x 360 30 fps at 704 x 288 30 fps at 352 x 288  |
| Multi-Streaming                   | Simultaneous triple streams   |
| Wide Dynamic Range                | Extreme WDR (135 dB)  |
| Image Enhancement                 | White Balance, Backlight compensation (BLC), Defogging  |
| Digital Noise Reduction           | 2D + 3D DNR   |
| Privacy Mask                      | 4 configurable regions  |
| Text Overlay                      | Yes   |
| Built-in Analytics                | Deep Learning : Smart Intrusion Protection, Smart Motion Detection, Face Detection, People Detection, Vehicle Detection, People Line Crossing Detection, People Enter Area Detection, People Exit Area Detection, Vehicle Line Crossing Detection, Vehicle Enter Area Detection, Vehicle Exit Area Detection, Tampering Detection, People Counting, Crowd Detection |
| Image Orientation                 | Flip, Mirror, Rotation (Corridor mode)(±90°, 180°)  |

## Audio

|            |   |
|------------|---|
| Audio Type | 2-way, Built-in Microphone, Line-in, Line-out |
|------------|---|

## Network

|                            |   |
|----------------------------|---|
| Network Protocol & Service | IPv4, IPv6, TCP, UDP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, NTP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, IGMP, ICMP, ARP, Bonjour, UPnP, SNMP, QoS, SSL/TLS, IEEE 802.1X |
| Ethernet Port              | 1 x Ethernet (10/100 Base-T), M12 connector   |
| Maximum User Connections   | 32  |
| Security                   | IP address filtering, HTTPS encryption, Password protected user level   |

## Event

|                |  |
|----------------|--|
| Event Trigger  | Video motion detection, Sound detection, Intelligent event detection                                 |
| Event Response | E-mail notification with snapshots, Save video or snapshot to storage, Upload snapshot to FTP server |

## Integration

|                 |   |
|-----------------|---|
| ONVIF Compliant | Yes, Profile S, Profile G, Profile T, Profile M |
| Web Browser     | IE 11, Microsoft Edge, Google Chrome, Firefox   |


**General**

|                       |  |
|-----------------------|--|
| Power Source          | DC 12V   |
| Power Consumption     | 6 W (DC)   |
| Dimensions            | (Ø x H): 110mm x 61mm (4.3" x 2.4")  |
| Environmental Casing  | Weatherproof (IP67), Vandal proof (IK10), Vibration proof (EN50155)  |
| Corrosion Protection  | Optional for project request. Chassis corrosion resistance at the seashore approximately 2-3 years.                                    |
| Operating Temperature | -30°C ~ 60°C (-22°F ~ 140°F)   |
| Operating Humidity    | ≤95% RH, non-condensing  |
| Surge Protection      | 4KV  |
| Approvals             | CE Class A, FCC Class A, IP67, IK10, EN 50155  |
| Color                 | White  |
| Material              | Metal  |
| Real-time Clock (RTC) | Yes  |
| Warranty              | 2 Year(s). For extended warranty offering, see <a href="http://www.acti.com/support/warranty">http://www.acti.com/support/warranty</a> |

## ► Photo Indication



## ► Dimension Diagram



Unit: mm [inch]