



4X1 HDMI SWITCH SPEC

SWT-UHD-4000

INTRODUCTION

The HDMI auto switch 4x1 can switch any one of the four HDMI input ports to the display terminal by remote control or button. It has an automatic switching function, that is, when a port is inserted into a new HDMI signal, it will automatically switch to the image of the port. And the time polling function supports 4 channels of HDMI signal cyclic switching, supporting 3 groups of time Settings 10 seconds, 15 seconds, 20 seconds. This HDMI switch supports HD formats including 720p, 1080i, 1080p, 4K/30Hz, 4K/60Hz.

FEATURES

- Support 3D video format;
- Support highest rate of 18Gbps and TMDS clock can be up to 600 MHz;
- **②** Support HDR:
- Support automatically switch HDMI input ports (Among the 4 ports preferentially switch to the port inserted last), when unplug a HDMI signal, preferentially switch to HDMI In1 interface, If HDMI In1 is not inserted, it automatically switch to port 2, and so on.
- Support HDMI input interface time polling function,10 seconds, 15 seconds, 20 seconds, 3 groups of time automatically switch
- Support multiple HDMI input signal sources, such as DVD, HDMI Media player, PS4, set-top box

SWT-U	HD-4000 Specification
HDMI Compliance	HDMI 2.0b
HDCP Compliance	HDCP 2.2 and HDCP 1.4
Video Bandwidth	18Gbps
Video Resolution	720p, 1080i, 1080p, 4K/30Hz, 4K/60Hz.
HDMI Audio	LPCM,DTS-HD/Dolby-
Formats	TrueHD/DTS/Dolby-AC3
Color Space	24/30/36bit Deep color
Output Port	1xHDMI Type A [19-pin female]
	1xL/R Audio out [3.5mm Stereo Mini-jack]
	1xOptical out [S/PDIF]
Input ports	4xHDMI Type A [19-pin female]
Power Supply	Input: AC100~240V 50/60Hz; Output:
	DC5V/1A
	(US/EU standards · CE/FCC/UL certified)
Power	600mA - Max.
Consumption	
Chassis Material	Metal
Chassis Color	Black
Operating	-10°C ~ 55°C
Temperature	
Storage	-10°C ~ 55°C
Temperature	
Humidity	20~85% RH (non-condensing)
Dimension	150mm(W)×67mm(D)×19mm(H)
Weight	175g

